



ADHESIVES AND GLUES DISPERSION PUTZ



Ready-to-use preparation paste
(produced in Germany)

Product description

Grigolin Dispersionsputz is a high-yield, cement-free dispersion preparation primer for interior and exterior finishes.

Thanks to its high elasticity and ease of application, it is particularly suitable for surface renovation and restoration.

Features

Pasty, easily workable, breathable, weather-resistant and solvent-free.

Supply and storage

Grigolin Dispersionsputz is supplied in 25 kg buckets on pallets of 24 buckets. The product can be used for up to 12 months from the date of production if stored undamaged in its packaging. Protect from frost.

DISPERSION PUTZ

Subfloor

The installation surfaces must be free of dust and dirt. Any traces of oil, grease, wax, etc. must be removed. Before applying Grigolin Dispersionsputz, make sure that the substrate is completely dry. If the application is carried out on compromised surfaces, an adhesion test should be carried out to check the result. Gypsum substrates must be completely dry before treatment.

Processing

Grigolin Dispersionsputz must be mixed before application. For work with reinforcement mesh, the product can be diluted up to 1% with clean water. The product must be applied with a metal trowel covering the entire surface with a thickness of about 3 mm. When the surface is completely dry, it is possible to apply a second coat of material, which is recommended for interventions on pre-existing walls. Wait at least one day after the surface has completely dried before applying the finish.

Drying time

Under normal conditions and depending on the ordered thickness, the drying time is approx. 24-48 hours. At low temperatures and high humidity, a possible drying time of several days must be considered.

Fields of application

Grigolin Dispersionsputz is a primer for preparing surfaces to be restored before finishing, also applied in two successive coats with the interposition of a glass fibre reinforcement mesh (e.g. RETE R 51 of approx. 60 g/sq.m. or a coating mesh of approx. 160 g/sq.m.). It can be applied to concrete substrates, plastered walls, mineral walls and dispersion paints. It can be used for reinforced skimming in Grigothem ETICS systems.

Warnings

Do not mix Grigolin Dispersionsputz with other substances. Avoid large temperature fluctuations during the setting phase. The product must be protected against frost and rapid drying. Grigolin Dispersionsputz cannot be used when the temperature is below +5°C or above +30°C.

DISPERSION PUTZ

TECHNICAL DATA	PERFORMANCE
Maximum application thickness	6 mm
Minimum application thickness	3 mm
Outdoor use	yes
Internal use	yes
Consumption per mm	1.00 kg/m ³
sd value	0,13 m
Capillary water absorption W24	0.04 kg/m ³ √ 24 h
Reaction to fire (DIN 4102)	class B1
Dilution	maximum 1%

v. 05/2021

I dati riportati si riferiscono alle prove di Controllo Qualità in condizioni ambientali normalizzate. Applicazioni pratiche di cantiere a seconda delle condizioni di esercizio possono rilevare dati sensibilmente modificati, pertanto le informazioni presenti nella Scheda hanno valore puramente indicativo in quanto l'utilizzatore deve sempre verificarne l'idoneità nell'impiego del prodotto assumendosi la responsabilità derivante dall'uso. Fornaci Calce Grigolin S.p.A. si riserva di apportare modifiche tecniche di qualsiasi genere senza alcun preavviso.